



COMMERCIAL

Refrigeration Equipment 3-Sliding Glass Door Full Height Merchandiser Refrigerator 83" Long

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738320 (KCHSGM72R)

3-Sliding Glass Door Full
Height Merchandiser
Refrigerator 83" Long

Short Form Specification

Item No. _____

3-sliding glass door refrigerator 83" long with exterior back and bottom panel in galvanized steel, exterior side, and top in painted steel; interior back, side top and bottom panels in 304 stainless steel. Electronic control. R290 gas in refrigeration circuit. ETL Safety and Sanitation certified. 3/5 Years warranty.


Main Features

- External digital temperature display.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Removable gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet completely insulated with high density polyurethane for low environmental impact.
- Back bottom mounted cooling unit guarantee an easy access and cleaning.
- Heavy duty Vinyl coated steel shelves.
- Interior LED light to save energy and for best internal visibility.

Construction

- Stainless steel interior and exterior, durable and easy to clean for daily commercial use.
- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Magnetic gasket removable without tools for easy cleaning.
- Pre-wired heavy duty power cord.
- Heavy duty rails for sliding doors

APPROVAL: _____



EI = Electrical connection

Electric

Supply voltage:

738320 (KCHSGM72R) 120 V/1 ph/60 Hz

Electrical power, max:

0.8 kW

Defrost Power

Plug type:

NEMA 5-15

Maximum Over-Current Protection (MOP):

0A

Capacity:

Gross capacity: 67.2 cu.feet

Key Information:

Capacity:	67.1924 cu.ft.
External dimensions, Width:	82 9/16" (2097 mm)
External dimensions, Depth:	31 7/8" (810 mm)
External dimensions, Height:	85 13/16" (2180 mm)
Internal Dimensions (depth):	25 3/16"
Internal Dimensions (height):	59 7/16"
Internal Dimensions (width):	76 3/8"
Shipping height:	88 3/16" (2240 mm)
Shipping weight:	728 lbs (330 kg)
Shipping volume:	139.31 ft ³ (3.95 m ³)

Refrigeration Data

Operating temperature min.:	35.2 °F
Operating temperature max.:	38.8 °F

Sustainability

Current consumption:	7 Amps
Refrigerant type:	R290