NEMA 6-20P

Plug

BAKERLUX™ - baking ahead of its time





XAFT-04HS-TD: BAKERLUX™ TOUCH Panel

Heavy-Duty Countertop Convection Oven with Digital Controls & Humidity

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy • NSF, MET to UL & CSA Standards Cadco Model XAFT-04HS-TD = UNOX Model XAFT-04HS-ETDV-US

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

FEATURES

- Advanced airflow design & automatically reversible fan for even baking
- USB programming capability
 9 baking steps
- Digital programmable controls: Time, Temperature, Humidity
- Wi-fi
 Data driven cooking
- Heat settings from 175°-500° F
- Saves up to 99 programs with graphic control panel
- Handles 4 half size sheet pans (not included)
- 4 wire shelves included
- Cooking chamber: 13-1/4" H x 19-1/4" W x 14" D (2.1 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use
- 2-5/8" between shelves

OPTIONAL ACCESSORIES: • XAKPT-08HS-C Proofer

- XAKHT-HCHS Ventless Hood
- XWKQT-00HS-E Stacking Kit

- 1 fan; 2 fan speeds
- Interior LED light
- Auto shut off when door is opened
- Includes electro valve for direct plumbed water
- "Cool-touch" double wall glass door opens from top
- Stackable with optional XWKQT-00HS-E Stacking Kit
- NSF; MET to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated
- Chef Support via phone
- 2 year Limited Warranty (one year On-site service & parts, 2nd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 3800 Watts / 16 Amps / Single Phase / 60Hz
- NEMA 6-20P Plug
- Freight class 200 NOTE: This model must ship by truck, not UPS
- Stands: OST-34A-C, OST-34A-CS
- Heavy-Duty 2-Oven Stand: OV-HDS

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Carton Dimensions	Cube	UPC#
XAFT-04HS-TD	Stainless	208-240	3800	16	w:235/8", h:195/8", d:29"	93 lbs.	139* lbs.	w:42", h:261/4", d:48"*	30.63*	654796-55141-5

*includes dimensions & weight (approx. 40 lbs.) of shipping skid