

**Refrigeration Equipment
Sandwich/Salad Preparation Table,
72" with 18GN 1/6 containers -
Stainless Steel (R290)**


ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



738258 (KCHST70.18)

3-door sandwich/salad preparation table for 18 GN 1/6 containers, 72", R290 refrigerant gas, +33/+41°F, stainless steel

Short Form Specification

Item No. _____

3-door sandwich/salad refrigerated preparation table. Exterior back panel in aluminium, exterior bottom panel in galvanized steel, side and top panels in 430 stainless steel; interior back, top panels and interior bottom panel in 304 stainless steel, worktop in 430 stainless steel. Built-in refrigeration unit and an insulated lid to maintain food freshness. Fin & Tube Condenser improves performance in high-temperature environments. Automatic Defrost Cooling System to provide worry-free performances. Full-depth cutting board of 71,7x11,4x0,5 in. Control panel, Vinyl-Coated Steel adjustable shelves, removable door gaskets and self-closing doors with 90-degree stay-open feature. Temperature range: +33/+41°F.

R290 gas in the refrigeration circuit.
ETL Safety and Sanitation certifications.
3/5 Years warranty.


Main Features

- External temperature display.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) - CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Full Depth cutting board.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmental impact.
- Heavy duty Vinyl coated steel shelves.

Construction

- Heavy duty casters.
- Insulated lid maintains food freshness.
- Holds 18 1/6 pans.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.

APPROVAL: _____



EI = Electrical connection
RI = Refrigerant Inlet
RO = Refrigerant Outlet

Electric

Supply voltage:
738258 (KCHST70.18) 115 V/1 ph/60 Hz
Electrical power, max: 0.7 kW
Plug type: NEMA 5-15

Capacity:

Gross capacity: 18 cu.feet

Key Information:

Door hinges: 1 Left+2 Right
External dimensions, Width: 71 11/16" (1822 mm)
External dimensions, Depth: 29 15/16" (760 mm)
External dimensions, Height: 43 1/4" (1097.5 mm)
Number and type of doors: 3 Full
Internal Dimensions (depth): 23 13/16"
Internal Dimensions (height): 23 1/2"
Internal Dimensions (width): 66 7/16"
Shipping height: 47 1/4" (1200 mm)
Shipping weight: 419 lbs (190 kg)
Shipping volume: 63.12 ft³ (1.79 m³)
Number and type of grids (included): 3 - 538x425/580x425
Type of external material: Stainless Steel
Type of internal material: Polystyrene
Warranty: 3 / 5 years

Refrigeration Data

Compressor power:
Refrigerant type: R290
Operating temperature min.: 32 °F
Operating temperature max.: 41 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost