



Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

TOP MOUNT REACH-IN FREEZERS

MODEL: MCFT-23FDHC MCFT-49FDHC MCFT-72FDHC



MCFT-23FDHC



MCFT-49FDHC



MCFT-72FDHC


Maxx Cold reach-in freezers are constructed from stainless steel, engineered with digital controls and polyurethane insulation for optimal temperature control and easy maintenance. Available in 1, 2 and 3 door configurations, each model features recessed handles, door locks and PE coated wire shelving with storage space for full size sheet pans.

FEATURES AND CONSTRUCTION

- Stainless steel exterior and interior
- Self-closing door(s) with easy to grip recessed handle(s)
- Field reversible door on single door model
- Automatic interior lighting
- Lock and key set for security
- Adjustable heavy-duty wire shelves (3 per section/door)
- Four (4) or six (6) 4" diameter swivel casters
- Electronic control panel with digital display
- Automatic defrost system
- Open door alert beeps if door has been open for five minutes
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Polyurethane foam insulation provides outstanding thermal regulation and energy efficiency

ELECTRIC

115V / 60Hz / 1Ph
(230V / 50-60Hz / 1Ph is available as an option)
6' (2m) NEMA 5-15P cord set included



NEMA 5-15P

3RD PARTY APPROVALS



Intertek

Certified to ANSI NSF 7



Intertek

Certified to ANSI UL 471



Meets Energy Star Guidelines

MAXX COLD WARRANTY (USA / CANADA)

Contact Maxx Cold for warranty statement at
TechnicalServices@TheLegacyCompanies.com or 877.368.2797


TEMPERATURE

Holding temperature -10°F to 10°F (-23°C to -12°C)

- Digital control system maintains optimum temperature
- Large evaporator and condenser for quick cooling and greater efficiency



MAXX COLD TOP MOUNT REACH-IN FREEZERS



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	HP	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MCFT-23FDHC	27" x 31" x 82" (681 x 787 x 2078 mm)	22.8" x 24.1" x 53.7" (578 x 613 x 1364 mm)	18.9 Cu Ft (535 L)	-10°F to 10°F (-23°C to -12°C)	4.9A	1/4	273 lbs (124 kg)	R-290a 2.82 oz (80 g)	1 / 3	115V / 60Hz / 1Ph
MCFT-49FDHC	54" x 31" x 82" (1370 x 787 x 2078 mm)	49.8" x 24.1" x 53.7" (1264 x 613 x 1364 mm)	42.8 Cu Ft (1212 L)	-10°F to 10°F (-23°C to -12°C)	6.8A	1/4	418 lbs (190 kg)	R-290a 4.44 oz (126 g)	2 / 6	115V / 60Hz / 1Ph
MCFT-72FDHC	81" x 31" x 82" (2060 x 787 x 2078 mm)	77.3" x 24.1" x 53.7" (1963 x 613 x 1364 mm)	66.7 Cu Ft (1889 L)	-10°F to 10°F (-23°C to -12°C)	8.4A	1/2	595 lbs (270 kg)	R-290a 5.22 oz (148 g)	3 / 9	115V / 60Hz / 1Ph

INSTALLATION

- Shorter caster options are available to lower the overall height of the unit